

JOBSITE360 POWER DISTRIBUTION

Power Distribution Box

Features

- Integrated GFCI Receptacles.
- Dedicated Quad USB receptacle for charging mobile devices.
- LED Indicator Light on the 50A Input Receptacle.
- Receptacles angled at 45° and protected with weatherproof covers.
- Internal components are located under a false top for easy access.
- Electrical components are easy to source and readily available.

Installation Guidelines

- We estimate each Lind power unit has a 100ft x 100ft (10,000ft²) area of coverage, assuming the use of 50' extension cords to power tools and equipment.



OVERVIEW

| | |
|--------------------------|---|
| Part Number | 92000 |
| Description | 50A Power Distribution Box (Spider Box) |
| Input | 50A 125/250V (California Standard) |
| Output | 50A 125/250V (California Standard) |
| Weatherproof Receptacles | 6 x 20A 125V GFCI Duplex (5-20R) 1 x 30A 250V Twist Lock (L6-30R) 1 x 4.8A Quad USB |
| Weight | 38 lbs |
| Dimensions | 23.5" W X 16.5" L X 15.5" H |
| Construction | Heavy-Gauge Powder Coated Steel |
| Approval | Approved to UL & CSA standards |
| Add-On Accessories | 91006 - 50 ft power cord 6/3 + 8/1 STOW w/ 50A plug and connector 91007 - 100 ft power cord 6/3 + 8/1 STOW w/ 50A plug and connector |