### **JOBSITE360 TEMPORARY LIGHTING**

## Beacon360 Blaze

#### **Features**

- Reduce installation points at a ratio of 25:1 compared to string-lights.
- Easily relocate or interchange with other Jobsite 360 lights throughout the site as the project progresses.
- Quickly transition onto a tripod or floor stand.
- A variety of mounting options.
- Dimmable to half-power.

### **Applications**

- All-purpose jobsite area light.
- Replace string-lights (250ft worth!)
- Replaces a 400W metal-halide light

# Recommended guidelines to meet OSHA standards

- Installation height: 8–15 feet
- Spacing: 50 feet
- 2,500 ft<sup>2</sup> coverage to 5fc





| OVERVIEW               |   |
|------------------------|---|
| Part Number            | LE360LED-25P25C   |
| Description            | 100W LED Low-Bay Wide Area Light  |
| Lumens                 | 14,300 @100% / 7,150 @ 50%  |
| Daisy-Chain            | <ul> <li>50 ft Daisy-Chain (25ft 5-15 Plug<br/>and 25ft 5-15 Triple Connector)</li> <li>Detachable from light head via<br/>Quick-Connect</li> </ul> |
| Quick-Connect          | Watertight 3-pin locking connector  |
| Amp Draw<br>(@120V)    | 0.83A   |
| Linkage Rating         | 14 units on a 15A/120V Circuit (equal to 35,000 ft² of coverage)  |
| Weight (light<br>head) | 4.5 lbs   |
| Construction           | Cast aluminum housing with polycarbonate lens   |
| Mounting options       | Eyebolt (included), 4-8 ft Tripod (-TR)<br>Floorstand (-FS), Magnet (-MAG)<br>Scaffold Clamp (-CLAMP)   |
| Temp to Perm<br>Option | LE360LED-BE, light head will come with a 10 ft cord with bare ends and 6 in stripped  |