JOBSITE360 TEMPORARY LIGHTING

Beacon360 Spark

Features

- Effortlessly branch off into individual rooms.
- Provides flexibility to install lights exactly where needed.
- 40% less energy usage compared to LED bulbbased string-lights.
- Easily relocated or interchanged with other Jobsite 360 lights throughout the site as the project progresses.

Applications

- Replace all types of string-lights
- Corridors
- Small/medium rooms
- Stairwells

Recommended guidelines to meet OSHA standards

- Installation height: 8–10 feet
- Spacing: 20 feet
- 400 ft² light coverage to 5fc





OVERVIEW	
Part Number	LE360LEDS-10P10C
Description	20W LED Modular String-Light
Lumens	2,400 lumens
Daisy-Chain	 20 ft Daisy-Chain Option (10 ft 5-15 Plug and 10 ft 5-15 Triple Connector) Detachable from light head via Quick-Connect.
Quick-Connect	Watertight 3-pin locking connector
Amp Draw (@120V)	0.17A
Linkage Rating	60 units on a 15A/120V Circuit (equal to 1,200 linear feet or 24,000 ft² of coverage)
Weight (light head)	1.5 lbs
Construction	High impact plastic & aluminum housing with polycarbonate lens.
Mounting options	Integrated molded mounting eyelet
Temp to Perm Option	LE360LEDS-BE , Light head will come with a 10-foot cord with bare ends and 6 inches stripped