

BEACON120 HIGH-BAY DATASHEET

Features

- Quick out-of-the-box plug & play installation.
- State-of-the-art DirectDrive technology eliminates the need for an external driver.
- Easily relocate or interchange with other Jobsite360 lights throughout the site as the project progresses.
- Connects to a daisy-chain with modular Quick Connect.
- Compact and lightweight, easy to uninstall, transport and store.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

Applications

- Area lighting for high ceiling heights
- Replaces a 400W metal-halide light

Recommended guidelines to meet OSHA standards

- Installation height: 16ft - 25ft
- Spacing: 50ft
- 2,500ft² light coverage to 5fc



OVERVIEW

Part Number	LE-HB120LED-25P25C
Description	120W LED High-Bay Light
Lumens	15,250 lumens
Daisy-Chain	<ul style="list-style-type: none">• 50ft Daisy-Chain (25ft 5-15 Plug and 25ft 5-15 Triple Connector)• Detachable from light head via Quick-Connect
Quick-Connect	Watertight 3-pin locking connector
Amp Draw (@120V)	1A
Linkage Rating	12 units on a 15A/120V Circuit (equal to 30,000ft ² of coverage)
Weight (light head)	2.6lbs
Construction	High strength lightweight aluminum housing with polycarbonate lens
Mounting options	Rugged stainless steel carabiner
Temp to Perm Option	LE-HB120LED-BE, light head will come with a 10ft cord with bare ends and 6in stripped