

BEACON360 BLAZE DATASHEET

Features

- Reduce installation points at a ratio of 25:1 compared to string-lights.
- Easily relocate or interchange with other Jobsite360 lights throughout the site as the project progresses.
- Quickly transition onto a tripod or floor stand.
- A variety of mounting options.
- Dimmable to half-power.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.



Applications

- All-purpose jobsite area light.
- Replace string-lights (250ft worth!)
- Replaces a 400W metal-halide light

Recommended guidelines to meet OSHA standards

- Installation height: 8ft - 15ft
- Spacing: 50ft
- 2,500ft² coverage to 5fc



OVERVIEW

Part Number	LE360LED-25P25C
Description	100W LED Low-Bay Wide Area Light
Lumens	14,700 @100% / 7,900 @ 50%
Daisy-Chain	<ul style="list-style-type: none">• 50ft Daisy-Chain (25ft 5-15 Plug and 25ft 5-15 Triple Connector)• Detachable from light head via Quick-Connect
Quick-Connect	Watertight 3-pin locking connector
Amp Draw (@120V)	0.83A
Linkage Rating	14 units on a 15A/120V circuit (equal to 35,000ft ² of coverage)
Weight (light head)	4.5lbs
Construction	Cast aluminum housing with polycarbonate lens
Mounting options	Eyebolt (included), 4-8ft Tripod (-TR) Floorstand (-FS), Magnet (-MAG) Scaffold Clamp (-CLAMP)
Temp to Perm Option	LE360LED-BE, light head will come with a 10ft cord with bare ends and 6in stripped