

BEACON360 SPARK DATASHEET

Features

- Effortlessly branch off into individual rooms.
- Provides flexibility to install lights exactly where needed.
- 40% less energy usage compared to LED bulb-based string-lights.
- Easily relocated or interchanged with other Jobsite360 lights throughout the site as the project progresses.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

Applications

- Replaces all types of string-lights
- Corridors
- Small/medium rooms
- Stairwells

Recommended guidelines to meet OSHA standards

- Installation height: 8ft - 10ft
- Spacing: 20ft
- 400ft² light coverage to 5fc



OVERVIEW

Part Number	LE360LEDS-10P10C
Description	20W LED Modular String-Light
Lumens	2,400 lumens
Daisy-Chain	<ul style="list-style-type: none">• 20ft Daisy-Chain (10ft 5-15 Plug and 10ft 5-15 Triple Connector)• Detachable from light head via Quick-Connect.
Quick-Connect	Watertight 3-pin locking connector
Amp Draw (@120V)	0.17A
Linkage Rating	60 units on a 15A/120V circuit (equal to 1,200 linear feet or 24,000ft ² of coverage)
Weight (light head)	1.5lbs
Construction	High impact plastic & aluminum housing with polycarbonate lens.
Mounting options	Integrated molded mounting eyelet
Temp to Perm Option	LE360LEDS-BE, light head will come with a 10ft cord with bare ends and 6in stripped

