BEACON980 FLOODLIGHT DATASHEET

Features

- Reinforced mounting yoke is adaptable to install on virtually any base.
- No expensive and breakable ballast.
- Available as retrofit kit to upgrade existing light towers and carts.
- State-of-the-art DirectDrive technology eliminates the need for external driver.
- Cart model features built-in generator pad, winch-assisted 12ft mast and foam filled rubber tires for completely safe and hassle-free operation.
- IP65 weather and wet location rated.
- 90V 277V input range.
- Approved to UL & CSA standards.

Applications

• Crane/pit lighting

General site lighting

- Concrete pours
- Excavations
- Light carts
- Demolition





OVERVIEW

Part Number	LE980LED
Description	200W Large Area Floodlight
Lumens	30,000 lumens
Amp Draw (@120V)	1.67A
Weight (light head)	16lbs
Cord	15ft 16/3 SJTW with 5-15 Plug
Construction	High strength lightweight aluminum housing with polycarbonate lens
Mounting options	Rugged steel adjustable bracket
LE980LED- TRW	Single light head, comes with a heavy-duty tripod with winch (max height: 12ft)
LE980LED- CART-W	Single light head, comes with a 2-wheel cart with winch (max height: 12.5ft)
LE980LED- CART-TD-W	Dual light head, comes with a 2-wheel cart with winch (max height: 12.5ft)

