

# HITCHING POST DATASHEET

Lind Equipment's **Hitching Post** is a portable charging station for battery powered equipment around the jobsite. When in transit or not in use, it can be folded and stowed to save on shipping costs and space. This product features innovations that make it compact, mobile, versatile, and most importantly safe.

## Features

- Integrated GFCI Receptacles.
- Foam filled tires.
- Built-in Beacon360 Blaze area light.
- Easily maintained.
- Fits through a standard doorway.
- Plug & play compatibility with other Lind products.
- Outdoor rated.
- Electrical components are easy to source and readily available.



## OVERVIEW

Part Number	LE-HP120-50CS
Description	50A Hitching Post (Equipment Charging Station)
Input	50A 125/250V TL (Cali Std)
Weatherproof Receptacles	10x 20A 125V GFCI Duplex (5-20R) 1x 15A 125V GFCI Singlet (5-15R)
Weight	250lbs
Dimensions	<b>Deployed:</b> 131" L x 30" W x 53" H <b>Stowed:</b> 75" L x 30" W x 53" H
Construction	Heavy-Gauge Powder Coated Steel
Approvals	Approved to UL & CSA standards
Add-On Accessories	<b>91006</b> - 50 ft power cord 6/3 + 8/1 STOW w/ 50A plug and connector  <b>91007</b> - 100 ft power cord 6/3 + 8/1 STOW w/ 50A plug and connector