

# BEACON120 HIGH-BAY DATASHEET

## Features

- Quick out-of-the-box plug & play installation.
- State-of-the-art DirectDrive technology eliminates the need for an external driver.
- Easily relocate or interchange with other Jobsite360 lights throughout the site as the project progresses.
- Light head and daisy-chain utilize modular theft resistant quick-connects.
- Compact and lightweight, easy to uninstall, transport and store.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

*\*Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations.*

## Applications

- Area lighting for high ceiling heights
- Replaces a 400W metal-halide light

## Recommended guidelines to meet OSHA & MOL/WorkSafe regulations

- **Installation height:** 16ft - 25ft
- **Spacing:** 50ft
- **Coverage Area:** 2,500ft<sup>2</sup> to 5fc



## OVERVIEW

Part Number	LE-HB120LED-25P25C-Q3 (120V & 277V)
Description	120W LED High-Bay Light
Lumens	15,250 lumens
Daisy-Chain (Q3 Model)	<ul style="list-style-type: none"><li>• 50ft 14/3 SJTW (25ft male quick-connect and 25ft triple female quick-connect) (15A Rated)</li><li>• Detachable from light head via quick-connect</li><li>• Watertight 3-pin locking connectors</li></ul>
Amp Draw	<ul style="list-style-type: none"><li>• @ 120V - 1A</li><li>• @ 277V - 0.44A</li></ul>
Linkage Rating	<ul style="list-style-type: none"><li>• @ 120V - 12 units on a 15A/120V circuit (equal to 30,000ft<sup>2</sup> of coverage to 5fc)</li><li>• @ 277V - 27 units on a 15A/277V circuit (equal to 67,500ft<sup>2</sup> of coverage to 5fc)</li></ul>
Weight (head)	2.6lbs
Construction	High strength lightweight aluminum housing with polycarbonate lens
Mounting Options	Rugged stainless steel carabiner
Temp to Perm Option	LE-HB120LED-BE, light head will come with a 10ft cord with bare ends and 6in stripped