

# BEACON360 SPARK DATASHEET

## Features

- Effortlessly branch off into individual rooms.
- Provides flexibility to install lights exactly where needed.
- Easily relocated or interchanged with other Jobsite360 lights throughout the site as the project progresses.
- Light head and daisy-chain utilize modular theft resistant quick-connects.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

*\*Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations.*

## Applications

- Replaces all types of string-lights
- Corridors
- Small/medium rooms
- Stairwells

## Recommended guidelines to meet OSHA & MOL/WorkSafe regulations

- **Installation height:** 8ft - 10ft
- **Spacing:** 20ft
- **Coverage Area:** 400ft<sup>2</sup> to 5fc



## OVERVIEW

<b>Part Number</b>	LE360LEDS-10P10C-Q3 (120V & 277V)
<b>Description</b>	20W LED Modular String-Light
<b>Lumens</b>	2,400 lumens
<b>Daisy-Chain (Q3 Model)</b>	<ul style="list-style-type: none"> <li>• 20ft 14/3 SJTW (10ft male quick-connect and 10ft triple female quick-connect) (15A Rated)</li> <li>• Detachable from light head via quick-connect</li> <li>• Watertight 3-pin locking connectors</li> </ul>
<b>Amp Draw</b>	<ul style="list-style-type: none"> <li>• @ 120V - 0.17A</li> <li>• @ 277V - 0.073A</li> </ul>
<b>Linkage Rating</b>	<ul style="list-style-type: none"> <li>• @ 120V - 60 units on a 15A/120V circuit (equal to 1,200 linear feet or 24,000ft<sup>2</sup> of coverage to 5fc)</li> <li>• @ 277V - 164 units on a 15A/277V circuit (equal to 3,280 linear feet or 65,600ft<sup>2</sup> of coverage to 5fc)</li> </ul>
<b>Weight (head)</b>	1.5lbs
<b>Construction</b>	High impact plastic & aluminum housing with polycarbonate lens.
<b>Mounting Options</b>	Integrated molded mounting eyelet
<b>Temp to Perm Option</b>	LE360LEDS-BE, light head will come with a 10ft cord with bare ends and 6in stripped