

BEACON360 SPARK DATASHEET

Features

- Effortlessly branch off into individual rooms.
- Provides flexibility to install lights exactly where needed.
- Easily relocated or interchanged with other Jobsite360 lights throughout the site as the project progresses.
- Light head and daisy-chain utilize modular theft resistant quick-connects.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

**Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations.*

Applications

- Replaces all types of stringlights
- Corridors
- Small/medium rooms
- Stairwells

Recommended guidelines to meet OSHA & MOL/WorkSafe regulations

- **Installation height:** 8ft - 10ft
- **Spacing:** 20ft
- **Coverage Area:** 400ft² to 5fc



OVERVIEW

Part Number	LE360LEDS-10P10C-Q3 (120V & 277V)
Description	20W LED Modular Stringlight
Lumens	2,400 lumens
Daisy-Chain (Q3 Model)	<ul style="list-style-type: none">• 20ft 14/3 SJTW (10ft male quick-connect and 10ft triple female quick-connect) (15A Rated)• Detachable from light head via quick-connect• Watertight 3-pin locking connectors
Amp Draw	<ul style="list-style-type: none">• @ 120V - 0.17A• @ 277V - 0.073A
Linkage Rating	<ul style="list-style-type: none">• @ 120V - 60 units on a 15A/120V circuit (equal to 1,200 linear feet or 24,000ft² of coverage to 5fc)• @ 277V - 164 units on a 15A/277V circuit (equal to 3,280 linear feet or 65,600ft² of coverage to 5fc)
Weight (head)	1.5lbs
Construction	High impact plastic & aluminum housing with polycarbonate lens.
Mounting Options	Integrated molded mounting eyelet
Temp to Perm Option	LE360LEDS-BE, light head will come with a 10ft cord with bare ends and 6in stripped