



# HITCHING POST DATASHEET

Lind Equipment's **Hitching Post** is a portable charging station for battery powered equipment around the jobsite. When in transit or not in use, it can be folded and stowed to save on shipping costs and space. This product features innovations that make it compact, mobile, versatile, and most importantly safe.

## Features

- Integrated GFCI receptacles.
- Foam filled tires.
- Built-in Beacon360 Blaze area light.
- Easily maintained.
- Fits through a standard doorway.
- Plug & play compatibility with other Lind products.
- Outdoor rated.
- Electrical components are easy to source and readily available.



## OVERVIEW

<b>Part Number</b>	LE-HP120-50CS
<b>Description</b>	50A Hitching Post (Equipment Charging Station)
<b>Input</b>	50A 125/250V TL (Cali Std)
<b>Weatherproof Receptacles</b>	10 x 20A 125V GFCI duplex (5-20R) 1 x 15A 125V GFCI Singlet (5-15R)
<b>Weight</b>	250lbs
<b>Construction</b>	Heavy-gauge powder coated steel
<b>Approvals</b>	Approved to UL & CSA standards <i>*Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations</i>
<b>Dimensions</b>	<b>Deployed:</b> 131" L x 30" W x 53" H <b>Stowed:</b> 75" L x 30" W x 53" H
<b>Add-On Accessories</b>	<b>91006 - 50ft power cord</b> 6/3 + 8/1 STOW w/ 50A plug and connector  <b>91007 - 100ft power cord</b> 6/3 + 8/1 STOW w/ 50A plug and connector

Part of the **Jobsite360** lineup for contractors.

Go To: [jobsite360.net/products](https://jobsite360.net/products)