BEACON120 HIGH-BAY DATASHEET

Features

- Quick out-of-the-box plug & play installation.
- State-of-the-art DirectDrive technology eliminates the need for an external driver.
- Easily relocate or interchange with other Jobsite360 lights throughout the site as the project progresses.
- Light head and daisy-chain utilize modular theft resistant quick-connects.
- Compact and lightweight, easy to uninstall, transport and store.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

**Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations.*

Applications

- Area lighting for high ceiling heights
- Replaces a 400W metal-halide light

Recommended guidelines to meet OSHA & MOL/WorkSafe regulations

- **Installation height:** 16ft - 25ft
- **Spacing:** 50ft
- **Coverage Area:** 2,500ft² to 5fc







OVERVIEW	
Part Number	LE-HB120LED-25P25C-Q3
Description	120W LED High-Bay Light
Lumens	15,250 lumens
Daisy-Chain (Q3 Model)	• 50ft 14/3 SJTW (25ft male quick-connect and 25ft triple female quick-connect) (15A Rated) • Detachable from light head via quick-connect • Watertight 3-pin locking connectors
Amp Draw	• @ 120V – 1A • @ 277V – 0.44A
Linkage Rating	• @ 120V - 12 units on a 15A/120V circuit (equal to 30,000ft² of coverage to 5fc) • @ 277V - 27 units on a 15A/277V circuit (equal to 67,500ft² of coverage to 5fc)
Weight (head)	2.6lbs
Construction	High strength lightweight aluminum housing with polycarbonate lens
Mounting Options	Rugged stainless steel carabiner
Temp to Perm Option	**LE-HB120LED-BE**, light head will come with a 10ft cord with bare ends and 6in stripped