

BEACON360 BLAZE DATASHEET

Features

- Easily relocate or interchange with other Jobsite360 lights throughout the site as the project progresses.
- Light head and daisy-chain utilize modular theft resistant quick-connects.
- Quickly transition onto a tripod or floor stand.
- A variety of mounting options.
- Dimmable to half-power.
- IP65 weather and wet location rated.
- 90V - 277V input range.
- Approved to UL & CSA standards.

**Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations.*

Applications

- All-purpose jobsite area light.
- Replace stringlights (250ft worth!)
- Replaces a 400W metal-halide light.

Recommended guidelines to meet OSHA & MOL/WorkSafe regulations

- **Installation height:** 8ft - 15ft
- **Spacing:** 50ft
- **Coverage Area:** 2,500ft² to 5fc



**The above LE360LED models come standard with a 15ft 18/3 SJTW cord with 5-15 Plug. The 50ft Q3 14/3 SJTW daisy-chain is available for these at request.*



OVERVIEW

Part Number	LE360LED-25P25C-Q3
Description	100W LED Low-Bay Wide Area Light
Lumens	14,700 @100% / 7,900 @ 50%
Daisy-Chain (Q3 Model)	• 50ft 14/3 SJTW (25ft male quick-connect and 25ft triple female quick-connect) (15A Rated) • Detachable from light head via quick-connect • Watertight 3-pin locking connectors
Amp Draw	• @ 120V - 0.83A • @ 277V - 0.37A
Linkage Rating	• @ 120V - 14 units on a 15A/120V circuit (equal to 35,000ft² of coverage to 5fc) • @ 277V - 32 units on a 15A/277V circuit (equal to 80,000ft² of coverage to 5fc)
Weight (head)	4.5lbs
Construction	Cast aluminum housing with polycarbonate lens
Temp to Perm Option	LE360LED-BE, light head will come with a 10ft cord with bare ends and 6in stripped